



## PureZone Machine

B I P O W E R 12/24V-50A



### Corredo standard / Standard outfits



- > PureZone Bipower (senza liquido)
- > PureZone Bipower (without liquid)



#### IT CARATTERISTICHE TECNICHE

- > Alimentazione duale (DC-AC)
- > 2 timer automatici (100ml/200ml)
- > Sensore di livello min-max
- > Protezione per uso con temperatura >45°C
- > Corpo in acciaio inox
- > Dimensioni: 30x15x22,5cm
- > Peso: 3,5kgs
- > Da utilizzare con prodotti specifici (SPIN US Clean o Killer Odor)

#### CORREDO BASE:

- A: Alimentatore da accendisigari 12 ÷ 24V DC
- B: Alimentatore 100 ÷ 240V AC 50-60Hz con cavo
- C: Convogliatore con tubo da 1mt

#### EN TECHNICAL FEATURES

- > Dual power supply (DC-AC)
- > 2 automatic timers (100ml/200ml)
- > Level sensor min-max
- > Protection against use with temperature >45°C
- > Stainless steel body
- > Dimensions: 30x15x22,5cm
- > Weight: 3,5kgs
- > For use with specific products (SPIN US Clean or Killer Odor)

#### BASIC KIT:

- A: Cigarette lighter power adapter 12 ÷ 24V DC
- B: Power supply 100 ÷ 240V AC 50-60Hz with cable
- C: Direct conveyor with 1mt hose



PUREZONE BIPOWER